

# **Air Control in Turbocharged Diesel Engines: Modelling, Identification & Calibration**

*October 20<sup>th</sup>, 2025*

**Silvio Simani**

*Department of Engineering, University of Ferrara*

*Via Saragat, 1E - 44122 Ferrara (FE) ITALY*

*Ph: +39 0532 97 4844. Fax: +39 0532 97 4844*

URL: [www.silviosimani.it](http://www.silviosimani.it)

Email: [silvio.simani@unife.it](mailto:silvio.simani@unife.it)

# Projects & Research Topics

- *Turbocharged Diesel Engine Modelling for Nonlinear Controller Design (2007-2014)*
- ✓ *Computerised Decision Support Systems for Oral Anticoagulant Treatment (OAT) Dose Management (2005-2007)*
- ✓ *Development of Fault Tolerant NGC (Navigation, Guidance & Control) Algorithms for CUAUV (Civil Unmanned Aerial Vehicle) Patrolling & Rescue Missions in Harsh Environment (2004-2025)*
- ✓ *Robotics & Medicine (2009 - 2011):*
  - *Mobile robots & SLAM - Simultaneous Localization & Mapping*
  - *Image-based visual servoing of robot manipulators - application to robotic surgery*


# Main Points

- Air-path control
- Turbocharged diesel engine
- Data-driven modelling
- Fuzzy modelling & system identification
- Controller calibration
- Simulation-based optimisation
- Emission reduction

# Introduction

- ✓ **Control scheme calibration & tuning for commercial diesel engines (boats, ships, farm tractors, ...)**
  - **Diesel engine modelling & identification**
    - **grey-box**: analytical approach & identification
    - **black-box**: fuzzy modelling & identification
  - **BOSCH Electronic Control Unit (ECU)**
    - Controller parameter calibration & tuning
    - Automated software tool for 'diesel calibration engineers'

# Project Logic Scheme



# Project Achievements

- Control-oriented simulation model
  - ❑ Grey-box model from real data (test-rig engine system)
  - ✓ Black-box engine model from real data (driving cycles)
- BOSCH controller implementation in Matlab/Simulink environments
- Automatic software (GUI) for controller calibration & parameter tuning

# The Diesel Engine & Its Emissions



# Diesel Usage

- ✓ Nearly all trucks, buses, trains, small ships
  - Good fuel efficiency
  - Lower greenhouse gas emissions
  - Reliability
  - Diesel price cheaper than gas (in Italy)
- ✓ Enormous size range:
  - 30 to 30,000 kW (40 to 40,000 hp)
- ✓ Usage has increased significantly in last 40 years

# Diesel Combustion

- ✓ Combustion: only two exhaust by-products?
  - $\text{CO}_2$  &  $\text{H}_2\text{O}$
- ✓ Unfortunately...
  - Diesel is not pure carbon & hydrogen:
    - Sulphur, nitrogen
  - Air is not pure oxygen
    - Nitrogen
- ✓ Engine combustion at high temperature & high pressure: environment to form **many chemical compounds**

# Diesel Emissions



Health Impact High to Low


- ✓ Particulate Matter (PM)
  - A product of incomplete combustion
- ✓ Oxides of Nitrogen ( $\text{NO} + \text{NO}_2 = \text{NO}_x$ )
  - $\text{NO}_x$  is a product of high temperature combustion
- ✓ & other minor compounds...
  - Carbon monoxide, sulphur dioxide ( $\text{SO}_2$ )

# Emission Reduction Strategies


- ✓ Reducing PM
  - Improve combustion efficiency
  - Increase peak combustion temperature
- ✓ Reducing NO<sub>x</sub>
  - Reduce peak combustion temperature
- **Air-to-Fuel (Mass) Ratio (AFR) Control**
  - Computer-controlled fuel & air injection rates
- **Exhaust Gas Recirculation (EGR)**
  - Combustion temperature reduction

# Adjust AFR or AMF

- AFR adjustment
  - Depends on torque
  - Engine speed
- AMF control
  - exploited in this project!



# NO<sub>x</sub> & PM Control




- 1) **AMF (Air Mass Flow) control**
  - *Reference, set point*
- 2) **Reduce Flame Temperature**
  - **EGR**
  - **TVA**

# Control Objectives

- **The control objective is to operate the TVA & EGR valves in a way such that:**
  - The engine meets the driver's *torque* demand
  - $\text{NO}_x$  & PM emissions are optimised (minimised)
  - Visible smoke generation is avoided
  
- **This can be achieved by regulating the Air Mass Flow (AMF) & the fraction of exhaust gases (EGR) in the intake manifold to the corresponding set-points**

# Set Point Generation



- Air Mass Flow (AMF) set-point is given as a function of engine fuelling ( $W_f$ ) & speed ( $N$ )
- It is computed to give minimum  $NO_x$  & PM emissions without any visible smoke
- In steady-state, AMF (& exhaust gas fraction) can be correlated to the engine outputs (e.g. compressor mass flow  $W_c$  & exhaust manifold pressure  $P_{man}$ ) through thermodynamic relationships (maps)


# Control-Oriented Diesel Engine Modelling



# Diesel Engine Modelling

- Process description & modelling
  1. **Grey-box approach**
    - Engine maps & look-up tables
    - Engine subsystems & components
  2. ***Black-box approach***
    - Fuzzy modelling & identification
- Model Validation





# Diesel Engine Scheme

## Inputs


- Engine speed ( $N$ )
- Fuel flow rate ( $W_{fuel}$ )
- Intake Temperature
- Engine Temperature (oil)


## Input Control Variables

- EGR command
- TVA command

## Main Output

- Air Mass Flow AMF ( $w_{c1}$ )





# **Diesel Engine**

## ***Grey-Box Modelling***

# MATLAB<sup>®</sup> / SIMULINK<sup>®</sup> Library

- Control-oriented engine simulation model
- MATLAB<sup>®</sup> / SIMULINK<sup>®</sup> environments
- Easy to use
- Reduced simulation time
- Control design, test, performance assessment
- Controller calibration & final tuning
- Real-time applications

# System Modelling

## ✓ State parameters

- $P, T, \rho, c, W, \dots$
- $N$  (speed)
- $X$  (chemical composition)
- ...

## ✓ Variables

- ...

## ✓ Equations


- Mass conservation
- Energy conservation
- Momentum conservation
- Motion quantity conservation
- State equations
- Transformation equations

# Components & Fluid-Dynamics

- ✓ Fluid machines (work exchange,  $\Pi \neq 0$  &  $\Phi = 0$ )
- ✓ Restrictions (no energy exchange,  $\Pi = 0$  &  $\Phi = 0$ )
- ✓ Heat exchangers & combustion chambers  
(thermal exchange,  $\Pi = 0$  &  $\Phi \neq 0$ )
- ✓ In-Cylinder Processes (thermal & work exchange,  
 $\Pi \neq 0$  &  $\Phi \neq 0$ )

# Exhaust Gas Recirculation (EGR)

## ➤ Valves & Restrictions



- ✓ Compressible Isentropic flow + flow coefficient  $C_d$



# Throttle Valve Actuator (TVA)


$$w_{th} = \begin{cases} \frac{k A_{th}(\alpha, N) p_{amb}}{\sqrt{RT_{up}}} \left(\frac{p_{th}}{p_{amb}}\right)^{1/\gamma} \sqrt{\frac{2\gamma}{\gamma-1} \left(1 - \left(\frac{p_{th}}{p_{amb}}\right)^{\frac{\gamma-1}{\gamma}}\right)} & \frac{p_{th}}{p_{amb}} > \bar{p} \\ \frac{k A_{th}(\alpha, N) p_{amb}}{\sqrt{RT_{up}}} \sqrt{\gamma} \left(\frac{2}{\gamma+1}\right)^{\frac{\gamma+1}{2(\gamma-1)}} & \frac{p_{th}}{p_{amb}} \leq \bar{p} \end{cases} \quad (1)$$

Algebraic Model


- $w_{th}$  is the flow through throttle
- From experimental data, the parameters  $k$  &  $A_{th}(\alpha)$  have to be *identified* (also as function of  $N$ )
  - Maps (look-up tables) or polynomials
- It is assumed that the downstream pressure  $p_{th}$  (unknown)  $p_{th} = p_{man}$

# Valve SIMULINK® Blocks

## Valves & restrictions: examples




**Pneumatic Valve EGR**



**Throttle Valve TVA**

**Control of the vacuum generator PWM & not the valve lift!**

# Manifold SIMULINK® Blocks




# Turbocharger (Turbine - Compressor)

➤ **Intake manifold**

➤ **Exhaust manifold**

➤ **Turbocharger**



# Engine Modelling Issues

## ➤ Engine subsystems contain unknown terms:

- Effective area (valves & restrictions, *i.e.* EGR/TVA):

$$A_{EGR}(x_{EGR}), A_{TVA}(x_{TVA})$$

- Volumetric efficiency (cylinder):  $\eta_v(N_e, P_{im})$

- Compressor/turbine isentropic efficiencies:

$$\eta_c(N_{tc}, T_{amb}, P_{im}/P_{amb}), \eta_t(x_{VGT}, N_{tc}, T_{em}, P_{out}/P_{em})$$

- Engine temperature:  $f(N_e, W_f)$

## ➤ Modelled by:

- Maps (1-D & 2-D) or polynomials



... about 1 year

# Engine Complete Description

## ➤ Engine Sub-models


- ✓ EGR
- ✓ TVA
- ✓ IM/EM
- ✓ Cylinders: Volumetric efficiency
- ☐ Turbine + Compressor: flow & efficiency maps
- ✓ Coolers: efficiency parameters

## ☐ Model Validation

- ☐ Completed but failed!



# Engine Complete Description (Cont'd)



# Diesel Engine *Black-Box* *Fuzzy Modelling*



# Fuzzy Modelling - FMID™

## ➤ Brief review

- Nonlinear regression & black-box modelling can be based on the partitioning data into *clusters*
- A cluster is a set of objects that are more similar to each other than to objects from other clusters

# FMID – Problem Formulation

- Given is a set of data
- Find the partitioning of the data into subsets (clusters), such that samples within a subset are more ‘similar’ to each other than to samples from other subsets
- Similarity is mathematically formulated by using a distance measure

# Fuzzy Clustering & Rules

**Takagi-Sugeno system  
(one model for each  
cluster  $i$ )**

$$y = a_i x + b_i$$

**Rule-based description**


If  $x$  is  $A_1$  then  $y = a_1 x + b_1$

If  $x$  is  $A_2$  then  $y = a_2 x + b_2$

If  $x$  is  $A_3$  then  $y = a_3 x + b_3$

If  $x$  is  $A_4$  then  $y = a_4 x + b_4$

Global fuzzy model: 
$$\sum_{i=1}^c \mu(x)(a_i x + b_i)$$



# Diesel Engine Application

## ➤ Input-output data

- Engine fuelling
- Engine temperature
- Intake temperature
- Engine speed
- EGR command
- TVA command

- AMF output signal

$$\text{Fuzzy model: } y(t) = \sum_{i=1}^c \mu(x(t))(a_i x(t) + b_i)$$

(4+2) Inputs –  $x(t)$



1 Output –  $y(t)$

... few weeks

- FMID™ for MATLAB® by Prof. Robert Babuska (Delft, The Netherlands). URL: <http://www.robertbabuska.com/>

# Identified Fuzzy Model FMID™


- Local models' order:  $n = 2$
- Cluster number:  $c = 9$




*Note:*  
 $c$  &  $n$  optimised  
 via a PEM  
 iterative scheme

# Fuzzy Model Simulation


- *Fuzzy model simulation*
- *Good performances for validation & several test data sequences*
- *Best Fit > 75% (in simulation & validation)*




# Fuzzy Model Simulation (zoom)




# Local Submodels (9 ARX models)



# BOSCH Controller 'Strategy' & Parameter Tuning




# Control Model Simulation



- ✓ Specific set-point assigned depending on fuel demand ( $W_f$ ) & speed ( $N$ )
- ✓ The controller actuates the EGR & TVA valves to correct the deviation between the actual ( $AMF$ ) & demanded variable

# Calibration in SIMULINK®



# BOSCH Controller Strategy


**Adaptive gains**

**FF: depends of fuel & RPM. Based on AMF static map inversion**


**Gain scheduler**

**Integrator reset logic**

**EGR/TVA split**




# Parameter Adaptation (Gain Adapt)



- BOSCH controller's main main idea is to correct the PI gains ( $K_i$  &  $K_p$ ) based on the error value & precompiled static maps
- Depends on engine fuelling, RPM, asp. temp & tracking error (actual & desired MAF)
- Fixed thresholds ( $K_{iPOS}$  &  $K_{iNEG}$ )

# Gain Scheduler: 'PI' Params



- It multiplies P & I gains & parameters
- Example:


$$P = \begin{cases} K_p^{(\text{scheduled})} \times e & \text{if } |e| < e_{\text{max}} \\ K_p^{(\text{scheduled})} \times e_{\text{max}} + K_{p,\text{max}} \times (e - e_{\text{max}}) & \text{otherwise} \end{cases}$$

- 'Bumpless' strategy

# BOSCH Controller *Calibration Strategy*




# Complete System (EU Driving Cycle)



# Technology


- Diesel engine driving cycle data
- MATLAB<sup>®</sup>/SIMULINK<sup>®</sup> interface
  - Calibration, optimisation; model, controller analysis, simulation & design
- ATI VISION<sup>™</sup>
  - Integrated calibration measurement solution for accessing ECUs
  - Table calibration
  - Memory emulation ( $\mu$ -controller)
  - On target rapid prototyping

# Parameter Correction



- **Matlab/Simulink**
  - ❖ **Parameter Estimation Toolbox**
    - **Optimisation Toolbox**
- **PEM algorithm**
- **MAF tracking optimisation**
- **Final validation**

# GUI: The Final Interface



➤ The user can select:

■ Data

■ Parameters

■ Optimisation algorithms

➤ The GUI tool 'suggests' the controller params & maps

# Parameter Correction (Example)

AirCtI\_facNQPar\_MAP

Giri [rpm]	Portata [mm <sup>3</sup> / cyc]															
	0	3	6	9	12	15	18	21	24	27	30	35	45	50	55	60
600	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
800	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1000	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1200	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1400	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1600	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1800	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2000	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2200	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2400	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2600	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2800	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

(Correction Map, i.e. the tuned parameter)

+

AirCtI\_facNQPar\_MAP\_Correzioni

Giri [rpm]	Portata [mm <sup>3</sup> / cyc]															
	0	3	6	9	12	15	18	21	24	27	30	35	45	50	55	60
600	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209	3.9209
800	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961	4.4961
1000	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713	5.0713
1200	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465	5.6465
1400	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217	6.2217
1600	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969	6.7969
1800	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721	7.3721
2000	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473	7.9473
2200	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225	8.5225
2400	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977	9.0977
2600	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729	9.6729
2800	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481	10.2481

=


(Nominal Map, IC)

AirCtI\_facNQPar\_MAP\_Corretta


Giri [rpm]	Portata [mm <sup>3</sup> / cyc]															
	0	3	6	9	12	15	18	21	24	27	30	35	45	50	55	60
600	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209	4.9209
800	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961	5.4961
1000	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713	6.0713
1200	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465	6.6465
1400	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217	7.2217
1600	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969	7.7969
1800	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721	8.3721
2000	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473	8.9473
2200	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225	9.5225
2400	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977	10.0977
2600	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729	10.6729
2800	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481	11.2481

(Controller Tuned Final Map)



# Map Correction (Example)



(provided by BOSCH)




(the map to be tuned)



Final controller map


Parameter Estimation Toolbox & Genetic Algorithm

# Controller Structure & Params



- ✓ Pre-control:  
1 map
- ✓ Gain adapt:  
2 maps
- ✓ *P*: 5 real variables
- ✓ *I*: 5 real variables

# Simulation Results (*EU Driving Cycle*)



# Alternative Procedures

## ➤ Related HD diesel engine control literature:

- Model-based predictive controller
- Fuzzy controller
- Neural networks
- Adaptive controllers

# Conclusions

- ✓ **TVA/EGR control design**
- ✓ **Application of the existent control law (BOSCH) to the identified engine model**
  - Black-box modelling (fuzzy system)
- ✓ **Identified system & controller integration**
  - EU Driving cycle data
  - Controller parameter tuning/optimisation
- **Matlab/Simulink GUI interface**
  - **Automated calibration software tool for ‘diesel calibration engineers’**
  - **ECU calibration & final tuning enhancement**

# Further Investigations

- Validation of the complete model of a multi-cylinder diesel engine
  - Turbocharger & related maps (grey-box)
- Control law implementation for the complete dynamic model
  - Control law with the real engine
  - Comparison with different control strategies (e.g. adaptive schemes)

# References

- *Introduction to Modeling and Control of Internal Combustion Engine Systems* by Lino Guzzella and Christopher H. Onder. Springer, August 2004. ISBN-10: 354022274X. ISBN-13: 978-3540222743.
- Control of diesel engines, by Guzzella, L.; Amstutz, A., *IEEE Control Systems Magazine*, Volume 18, Issue 5, Oct. 1998 Pages: 53 – 71.
- Modeling and Control of Turbocharged SI and DI Engines, by L. Eriksson. In: *Oil & Gas Science and Technology - Rev. IFP*. DOI: 10.2516/ogst:2007042

**FOR MORE INFO...**

**Visit Silvio Simani's personal web page:**

**<http://www.silviosimani.it/talks.html>**

***Thank you for your attention!***